

DUAL CENTRIFUGE

— ZENTRIMIX 380 R

HOMOGENIZING, MIXING AND MILLING – FAST AND EFFICIENT

The dual centrifuge ZentriMix 380 R allows many challenging laboratory tasks in research, development and analytics in a very efficient way or makes them possible for the first time. Examples are the rapid mixing of viscous materials, the production of nanoparticles in closed (sterile) vessels or tissue disruption. A particular advantage is the powerful cooling system for temperature-sensitive samples.



— HIGHLIGHTS

Easy expansion of additional applications

- (Nano-) Milling of samples
- QuEChERS-Analysis in one step
- Fast und homogeneous Mixing of highly viscous materials

Usage of cheap standard-vials

- saves money
- enables sterile Milling / Mixing / Storage of samples without extra effort
- eliminates cleaning time and effort vs. the standard mills or mixers

QuEChERS-Analysis saves 50-70% of time

- saves cleaning & additional procurement costs
- guarantees sterility of the sample (i.e. genetic analysis after Milling)

Further highlights

- very wide volume bandwidth when mixing (few ml to 2x 100 ml)
- Integrated cooling for sensitive samples
- delivers the same particle sizes as large agitator mills in pharmaceutical production for easy upscaling calculation

— FEATURES




- metal housing and lid
- viewing port in the lid
- powered one-hand lid lock
- lid dropping protection
- emergency lid lock release
- stainless steel chamber
- automatic rotor recognition
- brushless drive
- error display
- display in °C and °F possible
- imbalance switch-off
- backlit panel with actual values of all parameters
- auditory message after completion of the centrifugation run

TECHNICAL DATA

ZentriMix 380 R		
voltage ¹⁾	200 – 240 V 1 ~	110 – 127 V 1 ~
frequency	50 – 60 Hz	60 Hz
consumption	1,400 VA	1,600 VA
emission, immunity	EN/IEC 61326-1, class B	FCC class B
max. capacity	2 x 200 ml / 40 x 2.0 ml	2 x 200 ml / 40 x 2.0 ml
max. RPM (S rotor / Swing-out rotor, 4-place)	2,500 / 5,000 min ⁻¹	2,500 / 5,00 min ⁻¹
max. RCF (S rotor / Swing-out rotor, 4-place)	1,048 / 4,863	1,048 / 4,863
dimensions (WxDxH)	472 x 759 x 418 mm	472 x 769 x 418 mm
weight	approx. 81.5 kg	approx. 89 kg
Cat. No.	3200	3200-01

1) Other voltages on request.

AVAILABLE ROTORS


ROTORS		angle	max. RPM	max. capacity	Cat. No.	page
	H rotor, 2-place	40°	1,500 min ⁻¹	2 x 200 ml	3206	3
	S rotor, 2-place	40°	2,500 min ⁻¹	2 x 200 ml	3205	3
	Swing-out rotor, 4-place	40°	5,000 min ⁻¹	4 x 250 ml	3234	4

H ROTOR, 2-PLACE | 3206



Rotor

max. RPM max. RCF	1,500 min ⁻¹ 377
max. capacity	2 x 200 ml
run-up run-down, braked in sec	22 24
angle temperature in °C ²⁾	40° +20
Cat. No.	3206



Vessels

capacity in ml	15	50	150	200
Ø x L in mm	17 x 120	29 x 115	68 x 60	68 x 79
max. RCF ²⁾	377	377	377	377
radius in mm	150	150	150	150
Cat. No.	tubes	jars with screw cap		



Adapter

vessels per rotor	6	6	2	2
Cat. No.	3218	3218	3221-A	3221-A



S-ROTOR, 2-PLACE | 3205



Rotor

max. RPM max. RCF	2,500 min ⁻¹ 1,048
max. capacity	2 x 200 ml
run-up run-down, braked in sec	35 35
angle temperature in °C ²⁾	40° +20
Cat. No.	3205




Vessels

capacity in ml	2.0	10	150	200
Ø x L in mm	11 x 45.5	25.5 x 49	68 x 60	68 x 79
max. RCF ²⁾	1,048	1,048	1,048	1,048
radius in mm	150	150	150	150
Cat. No.	-	-	jars with screw cap	



Adapter

vessels per rotor	4	4	2	2
Cat. No.	3236	3211	3221-A	3221-A



Removal aid for Twist-Top disk 3236.

3210

37) Conical 2 ml Sarstedt PP microlitre tubes with screw cap
(Art.No. 72.693.005)

38.1) Please only use polypropylene vessels in accordance with ISO 8362 (No Glass!), to fit into the adapter the height of the vessel including crimp cap and stopper should be 48.5 mm.

39) All S Rotor adapters can also be used in the H Rotor.

— SWING-OUT ROTOR, 4-PLACE | 3234



Rotor

max. RPM max. RCF	5,000 min ⁻¹ 4,863
max. capacity	4x250 ml
run-up run-down, braked in sec	42 27
angle	90°
Cat. No.	3234















Bucket

lid bioseal ⁵⁾	1751
Cat. No.	1752







Vessels

												
capacity in ml	10	9	15	94	100	100	250	15	50	30	50	250
Ø x L in mm	25.5x49	14x100	17x100	38x102	40x115	44x100	65 x 115	17x120	29 x 115	25x110	29x115	61 x 122
max. RCF ⁷⁾	top / bottom	4,695	4,668	4,668	4,807	4,640	4,640	4,863	4,863	4,528	4,752	4,863
radius in mm	top / bottom	168	167	167	172	166	166	174	174	162	170	174
Bestell-Nr.	-	tubes⁷⁾						tubes with screw cap				



Adapter

												
boring Ø x L in mm	26x33	17.5x61	17.5x61	38.5x80	41x97	45x87	66x104.5	17x84	30x84	26.5x72	30x80	62x100
vessels per rotor	24	52	52	8	4	4	4	36	16	20	16	4
Cat. No.	3235	1763-A	1763-A	1777	1767	1766	1768	1771-A	1772-A	1779	1774-A	1769

5) Tested by the TÜV in conformity with DIN EN 61010, section 2-020.

7) Please note that the RCF values indicated refer only to rotor performance. The max. permissible RCF of tubes used should be verified with the individual manufacturers.

38.2) Polypropylene vessels in accordance with ISO 8362.

40) At temperatures of over +40 °C and / or when not filled to capacity, bottles may warp during centrifugation.



CERTIFICATIONS / REGISTRATIONS

Product certification: Company certifications:



DOWNLOADS

[↓ Operating Manual – ZentriMix 380 R](#)

[↓ ZentriMix 380 R brochure](#)

[↓ General Catalog](#)

DIMENSIONS – ZENTRIMIX 380 R

